

3.If your local, state and / or federal laws and regulations permit mounting the Device your car windows, we recomment affixing it to the lower right or left corner of the rear windshield of your car. Males user the Device does not block your view of the road and does not obstruct your vision in any way. The device is intended to be used in The device is meant for solely social intended to be used for negative a 4.Do not use the Device and / or the App while driving because it may distract you fror paying attention to the road ahead. Choose what to display prior to starting your driv Do not handle your smart phone while driving. Keep your eyes on the road at all times Package contains
Lighter Plug (leng
User Manual and 5. When the Device is turned on and in use at night, adjust the brightness of the display to the minimum not to blind and distract other drivers on the road or simply turn off the Technical data 6.Do not leave the Device in your car, even if it's turned off, under the direct sun light because it can lead to overheating of the battery and its explosion, which in turn may cause severepersonal injuries to the driver and / or passengers of the car or other pe-neatry, including death. 7.When in use, the Device must remain inside your vehicle, home or any other place or at all times. Protect it from water, humidity and other elements. Do not store the Devin environments that are too hot, too cold or too humid to protect the battery. Compatibility iOS version 10.0 and higher Android version 6.0 and high Getting started ake sure that the Device sand other visual dama-Switching the device on

Off Button and hold it for 2 seconds, as shown in figure utton and how.. gntness: bUUCC outdoor LEDs. ximum Brightness depends on firmware ar x. brightness with full white color can be fr pend on hardware and firmware versions) rking brightness can be from 0 to 5800Cd Power
Car Cigarette Plug.
Onboard car power 12V
Maximum power consul able battery pack Mobile Application Materials Case: ABS + PC Mount: POM, 2 la suction cups uttons Control ext image ower On / Power Off / Check Battery Pairing the Device with your smartphone Device mounting on rear or side window Adhesive mount is designed for along-termmounting, and it's difficult to remove it.

Thoses mounting place carefully before you attach your Device. While attaching it Device to the window, chose such a place or near or side window so that the devides not impede, divert the driver and obscure the road and driver's vision. ng several devices simultaneously, ch es, emojis, Gif, text, and edit and sav display different images, emojis, Off, text, and odit and save them.

If this is your first MojipicDevice which you connect to your smartphone, ret
Terms of Use you are prompted to in the Mojipic App
1 Switch on the Device and place it near your smartphone.
2 Enable Blustooth function on your mobile device and choose Mojipic for p
3 When pairing an additional device with your smartphone, choose new dev
isst of the Mobile App and click New Search.
4. Following the instruction in the Mobile App set: brightness, contend display
control and commands, suit out mol fisynchronize the bevice with the Mobi
content from the main App catalogue has been afreedy uploaded on it.

1. As the Device owner, You shall be fully responsible for the images, i
you display on your Device!

2. Brightness of your Device must not cause difficulties to a driver be
especially at night time, therefore use minimum brightness level, o
Device mountain are mounting the adhesive holder to the windshield, make sure that ambient berature is within the range from 21°C to 38°C (70°F to 100°F). temperature is within the range from 2°PC to 3°PC (7°PT to 10°PT).

Clean the windshield by wiping it with lint free cloth steeped in water or spirit. Reer or side window must be clean, free from dust, was, greate or other coatings, and the real coating and the state of the window wind with un bound or separately, i.e. first you after the real coating and the state of the window wind yet with un bound or separately, i.e. first you after the real coating and the state of the real coating and the real coati Device mounting

Place the Device at the left or right corner of research to the second visibility. Adhesive base is very sticky. Prevent contact of the adhesive base with the windshield, until you choose the final position of the mount. Foress the mount end stightly one-by-one to the rear or side window in for 30 seconds. Then turn the pressure arm of the suction cup into pail suction cup it will ensure tight contact of adhesive base with glass. Should any of the suction cups or both come off the car window as a result of th incorrect initial fixation or improper operation, or by any other reason, you must degreese the glass, and wash the suction cup surface with water and dry it off, then fix it again. Device On/Off Device manual switching-on Before using the Device with battery power, fully charge the battery. Better to any unity of the property of the period of the p 1. Find On/Off button on the Device case. Press and hold it for 2 seconds.
2. The welcome image will appear, then you! I see the status of built-in rect.
3. Then 'E' image will appear witch means the Device flash memory is empuloaded images will appear.
4. The Device is on and ready for use. Device manual switching-off NOTE!
If the Device is powered from a source connect
off, the Device may stop charging, depending.
1. Press and hold On/Off button for 2 second. On/Off switching using the App.
mobile App to switch On/Off Device Also You can use Mojple motione Apt to switch on Just Purice

Perice On/Off switching using voice commands

1. To enable Device voice control, first switch the Device on manually.

2. Then using the Mobile App you can switch the device on and off using voice commodities of the provided on the manually switched on to enable voice commands and On/Off voice switching Device memory cleaning Device memory creaming To fully clean the memory of the Device from all downloads tab within the App and click on "Clear Device" link.

TROUBLESHOOTING nloaded content, go to the Setting Molipic DeviceFAILED TO SWITCH ON
Meles sure that the Molipic Devices charged. To charge the devic
cable. You can also use mains charge at home or car charger cotime adapter is not included in standard package of any other.
Molipic Device DOES NOT RESPOND TO BUTTONS PRESSING
Thate a paper clip, insert it in the Reset hole and push one time.
Blinking or improper image display on the Device
Take a paper clip, insert it in the Reset hole and push one time.
The image is not uploaded from the App
Switch the Device off.
Switch the Device back on,
reset the Device
clean the Device using the Mobile App
App Not Loading.
Restart the App and the Device.

The Device is DAMAGED Connection of car power cable to the device and battery charging.

Charging cable is supplied as part of device package. Connect 5.5 jaciplug to the

connector at the bottom of the Device book, the other end insert in car plugin 12/.

You can also use power cable 20/0 and 5.5 jack plug to charge the device at home, that

compatible with USB voltage 5-5.2 V. current intensity - 2-3.6) specification. Connect tr

cable to USB-connector - the battery will start charging automatically.

Charging indication will be displayed on the main Mojpic screen. Short press on the On

button (1 on figure above) will show current charge status. It takes 5-6 hours until the

battery is fully charged. Nead answers to unter it respecting as a superior and unplug the cable if the battery is fully charged.

10 not leave the Molpic Device in an enclosed space where the temperature can re over 80 degrees Celsius and 170 degrees for can go below 0 degrees Celsius and 170 d Use charging cable to charge to fully charged. if handled in-correctly!
Use only the prepacked battery charge
Do not dig the battery into water.
Do not digssemble the battery and to both of the battery and to not overhead the battery and on to Do not leave the battery and not Do not leave the battery in an enclose of degrees Elous and 176 degrees F. Do not cover body case holes, intende Do not close battery volt-free contact.
Try keeping the battery uout of impact I cause damaney. BATTERY DISPOSAL

Mostrechargeable Li-in batteries are considered non-hazardous waste and can be disposed as a regular domestic waste Mendatory battery recycling laws are adopted in many countries. Explore local laws to be sure that rechargeable batteries may be disposed with domestic waste? For afiel disposal of Li-in batteries prevent their contact with oth metals. By covering them with a tape. This will prevent fire risk while handling the disposal Correct battery disposal will help avoid a potential impact on the environment, as well as contribute to components repeated use after recycling. Ask your local authorities for independent and a potential interest in the disposal contribute to components repeated use after recycling. Ask your local authorities for contribute to components repeated use after recycling. Ask your local authorities to disposal information. Device Disposali if the Device bisposali if the Device has reached the end of its service life, it should be disposed in accorda with regulations, rules and methods which are applied at the place of the disposal Don rot discarch the device together with your regular domestic waste. At the end of the Device service life, take it to the disposal or recycling centre, if you rules and regulations of your region, it will help avoid a potential impact on the environment, as well as contribute to components repeated use after recycling. Ask local authorities for disposal information. ees Lesius or 6,24 degrees harmenierini Following these recommendations will ensure trouble-free operation Leave the Mojipic Device face down to prevent damaging the LED panel at the LED panel does not touch any surface. Sure that a car or premises, where the Mojipic device is used, are free fro ed, wipe the device with a soft lint free cloth. If the LED cells, clean them with an air stream. Do CUSTOMER SERVICE t customer service. To contact Mojipic cu